



SAFETY DATA SHEET

1. Identification

Product identifier 2K URETHANE NON-SANDING SEALER - WHITE
Other means of identification
Product code IMP4852
Recommended use Acrylic Urethane Sealer
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name REFINISH DISTRIBUTORS ALLIANCE, INC.
Address P.O. BOX 10431
JACKSON, TN 38308
Telephone 731-394-9366
Website www.rda-impact.com

EMERGENCY PHONE 24 Hrs. 800-424-9300 ChemTrec

2. Hazard(s) identification

| | | |
|------------------------------|--|-------------|
| Physical hazards | Flammable liquids | Category 2 |
| Health hazards | Acute toxicity, oral | Category 4 |
| | Skin corrosion/irritation | Category 2 |
| | Serious eye damage/eye irritation | Category 2A |
| | Germ cell mutagenicity | Category 1B |
| | Carcinogenicity | Category 1A |
| | Reproductive toxicity (the unborn child) | Category 2 |
| | Specific target organ toxicity, repeated exposure | Category 1 |
| Environmental hazards | Hazardous to the aquatic environment, acute hazard | Category 3 |
| | Hazardous to the aquatic environment, long-term hazard | Category 3 |
| OSHA defined hazards | Not classified. | |
| Label elements | | |



Signal word

Danger

Hazard statement

Highly flammable liquid and vapor. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause genetic defects. May cause cancer. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Rinse mouth. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

Storage

Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

75.75% of the mixture consists of component(s) of unknown acute oral toxicity. 87.8% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 87.8% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|-----------|
| parachlorobenzotrifluoride | | 98-56-6 | 20 - < 40 |
| Titanium Dioxide | | 13463-67-7 | 10 - < 30 |
| Acetone | | 67-64-1 | 5 - < 20 |
| Talc | | 14807-96-6 | 5 - < 20 |
| Glycol Ether PM Acetate | | 108-65-6 | 5 - < 10 |
| Toluene | | 108-88-3 | 5 - < 10 |
| Aluminum Hydroxide Regulatory | | 21645-51-2 | 0 < 5 |
| Crystalline Quartz Regulatory | | 14808-60-7 | 0 < 5 |
| Dibutyltin Dilaurate | | 77-58-7 | 0 < 5 |
| Ethylbenzene | | 100-41-4 | 0 < 5 |
| Naphtha, Petroleum, Heavy Alkylate | | 64741-65-7 | 0 - < 5 |
| Phosphoric Acid Regulatory | | 7664-38-2 | 0 < 5 |
| Silica | | 7631-86-9 | 0 < 5 |
| Solvent Naphtha, petroleum, light aromatic | | 64742-95-6 | 0 < 5 |
| Tremolite (Non-asbestiform) | | 14567-73-8 | 0 - < 5 |
| Xylene | | 1330-20-7 | 0 - < 5 |
| Other components below reportable levels | | | 5 - < 10 |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

| | |
|---|--|
| Most important symptoms/effects, acute and delayed | Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed. |
| General information | Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. |

5. Fire-fighting measures

| | |
|--|--|
| Suitable extinguishing media | Alcohol resistant foam. Water fog. Carbon dioxide (CO ₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire fighting equipment/instructions | In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | Highly flammable liquid and vapor. |

6. Accidental release measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination. |

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

| Components | Type | Value |
|---|------|----------------|
| Tremolite (Non-asbestiform) (CAS 14567-73-8) | STEL | 1 fibers/cm3 |
| | TWA | 0.1 fibers/cm3 |

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---|------|------------------------|-------------|
| Acetone (CAS 67-64-1) | PEL | 2400 mg/m3 1000 ppm | |
| Dibutyltin Dilaurate (CAS 77-58-7) | PEL | 0.1 mg/m3 | |
| Ethylbenzene (CAS 100-41-4) | PEL | 435 mg/m3 100 ppm | |
| Naphtha, Petroleum, Heavy Alkylate (CAS 64741-65-7) | PEL | 400 mg/m3 100 ppm | |
| Phosphoric Acid Regulatory (CAS 7664-38-2) | PEL | 1 mg/m3 | |
| Titanium Dioxide (CAS 13463-67-7) | PEL | 15 mg/m3 | Total dust. |
| Xylene (CAS 1330-20-7) | PEL | 435 mg/m3 100 ppm | |

US. OSHA Table Z-2 (29 CFR 1910.1000)

| Components | Type | Value |
|------------------------|---------|---------|
| Toluene (CAS 108-88-3) | Ceiling | 300 ppm |
| | TWA | 200 ppm |

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Type | Value | Form |
|--|------|------------------------|----------------------------|
| Crystalline Quartz Regulatory (CAS 14808-60-7) | TWA | 0.3 mg/m3 | Total dust. |
| | | 0.1 mg/m3 2.4 mppcf | Respirable. Respirable. |
| Silica (CAS 7631-86-9) | TWA | 0.8 mg/m3 20 mppcf | |
| Talc (CAS 14807-96-6) | TWA | 0.3 mg/m3 | Total dust. |
| | | 0.1 mg/m3 20 mppcf | Respirable. |
| | | 2.4 mppcf | Respirable. |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|--|------|----------------|----------------------|
| Acetone (CAS 67-64-1) | STEL | 750 ppm | |
| | TWA | 500 ppm | |
| Aluminum Hydroxide Regulatory (CAS 21645-51-2) | TWA | 1 mg/m3 | Respirable fraction. |
| | | | |
| Crystalline Quartz Regulatory (CAS 14808-60-7) | TWA | 0.025 mg/m3 | Respirable fraction. |
| | | | |
| Dibutyltin Dilaurate (CAS 77-58-7) | STEL | 0.2 mg/m3 | |
| | TWA | 0.1 mg/m3 | |
| Ethylbenzene (CAS 100-41-4) | TWA | 20 ppm | |
| | | | |
| Phosphoric Acid Regulatory (CAS 7664-38-2) | STEL | 3 mg/m3 | |
| | TWA | 1 mg/m3 | |
| Talc (CAS 14807-96-6) | TWA | 2 mg/m3 | Respirable fraction. |
| | TWA | 10 mg/m3 | |
| Toluene (CAS 108-88-3) | TWA | 20 ppm | |
| Tremolite (Non-asbestiform) (CAS 14567-73-8) | TWA | 0.1 fibers/cm3 | Fiber. |
| | | | |
| Xylene (CAS 1330-20-7) | STEL | 150 ppm | |
| | TWA | 100 ppm | |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|--|------|---------------------------------|------------------|
| Acetone (CAS 67-64-1) | TWA | 590 mg/m3 250 ppm | |
| | | | |
| Crystalline Quartz Regulatory (CAS 14808-60-7) | TWA | 0.05 mg/m3 | Respirable dust. |
| | | | |
| Dibutyltin Dilaurate (CAS 77-58-7) | TWA | 0.1 mg/m3 | |
| | | | |
| Ethylbenzene (CAS 100-41-4) | STEL | 545 mg/m3 | |
| | TWA | 125 ppm 435 mg/m3 100 ppm | |
| Naphtha, Petroleum, Heavy Alkylate (CAS 64741-65-7) | TWA | 400 mg/m3 | |
| | | | |
| Phosphoric Acid Regulatory (CAS 7664-38-2) | STEL | 100 ppm 3 mg/m3 | |
| | TWA | 1 mg/m3 | |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|------------------------|------|----------------------|-------------|
| Silica (CAS 7631-86-9) | TWA | 6 mg/m3 | Respirable. |
| Talc (CAS 14807-96-6) | TWA | 2 mg/m3 | |
| Toluene (CAS 108-88-3) | STEL | 560 mg/m3 | |
| | | 150 ppm | |
| | TWA | 375 mg/m3 100 ppm | |

US. Workplace Environmental Exposure Level (WEEL) Guides

| Components | Type | Value |
|--|------|--------|
| Glycol Ether PM Acetate (CAS 108-65-6) | TWA | 50 ppm |

Biological limit values**ACGIH Biological Exposure Indices**

| Components | Value | Determinant | Specimen | Sampling Time |
|-----------------------------|-----------|---|---------------------|---------------|
| Acetone (CAS 67-64-1) | 50 mg/l | Acetone | Urine | * |
| Ethylbenzene (CAS 100-41-4) | 0.15 g/g | Sum of mandelic acid and phenylglyoxylic acid | Creatinine in urine | * |
| Toluene (CAS 108-88-3) | 0.3 mg/g | o-Cresol, with hydrolysis | Creatinine in urine | * |
| | 0.03 mg/l | Toluene | Urine | * |
| | 0.02 mg/l | Toluene | Blood | * |
| Xylene (CAS 1330-20-7) | 1.5 g/g | Methylhippuric acids | Creatinine in urine | * |

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

| | |
|--|-----------------------------------|
| Dibutyltin Dilaurate (CAS 77-58-7) | Can be absorbed through the skin. |
| Glycol Ether PM Acetate (CAS 108-65-6) | Can be absorbed through the skin. |
| Toluene (CAS 108-88-3) | Can be absorbed through the skin. |

US - Minnesota Haz Subs: Skin designation applies

| | |
|------------------------------------|---------------------------|
| Dibutyltin Dilaurate (CAS 77-58-7) | Skin designation applies. |
| Toluene (CAS 108-88-3) | Skin designation applies. |

US - Tennessee OELs: Skin designation

| | |
|------------------------------------|-----------------------------------|
| Dibutyltin Dilaurate (CAS 77-58-7) | Can be absorbed through the skin. |
|------------------------------------|-----------------------------------|

US ACGIH Threshold Limit Values: Skin designation

| | |
|------------------------------------|-----------------------------------|
| Dibutyltin Dilaurate (CAS 77-58-7) | Can be absorbed through the skin. |
|------------------------------------|-----------------------------------|

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

| | |
|------------------------------------|-----------------------------------|
| Dibutyltin Dilaurate (CAS 77-58-7) | Can be absorbed through the skin. |
|------------------------------------|-----------------------------------|

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state Liquid.

Form Liquid.

Color White

Odor Solvent.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -138.82 °F (-94.9 °C) estimated

Initial boiling point and boiling range 132.89 °F (56.05 °C) estimated

Flash point -4.0 °F (-20.0 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 1.3 % estimated

Flammability limit - upper (%) 12.8 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 854.86 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 869 °F (465 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 2.00 g/cm³ estimated

Flammability class Flammable IB estimated

Percent volatile 50.59 w/w % By Weight

64.57 v/v % By Volume

Specific gravity 2.00 estimated

VOC (Weight %) 1.08 lb/gal (Actual VOC - With Water With Exempts)

2.23 lb/gal (Regulatory VOC - Less Water Less Exempts)

129.51 g/L (Actual VOC - With Water With Exempts)

267.10 g/L (Regulatory VOC - Less Water Less Exempts)

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong acids. Acids. Strong oxidizing agents. Halogens.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact Causes skin irritation.
Eye contact Causes serious eye irritation.
Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

| Components | Species | Test Results |
|---|---------|--|
| Acetone (CAS 67-64-1) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | 20000 mg/kg 20 ml/kg |
| Inhalation | | |
| LC50 | Rat | 76 mg/l, 4 Hours 50.1 mg/l, 8 Hours |
| Oral | | |
| LD50 | Mouse | 3000 mg/kg |
| | Rabbit | 5340 mg/kg |
| | Rat | 5800 mg/kg |
| Aluminum Hydroxide Regulatory (CAS 21645-51-2) | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| Dibutyltin Dilaurate (CAS 77-58-7) | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | 175 mg/kg |
| Ethylbenzene (CAS 100-41-4) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | 17800 mg/kg |
| Oral | | |
| LD50 | Rat | 3500 mg/kg |
| Naphtha, Petroleum, Heavy Alkylate (CAS 64741-65-7) | | |
| Acute | | |
| Inhalation | | |
| LC50 | Rat | 61 mg/l, 4 Hours |
| Oral | | |
| LD50 | Rat | > 25 ml/kg |
| Phosphoric Acid Regulatory (CAS 7664-38-2) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | 2740 mg/kg |

| Components | Species | Test Results |
|------------------------|---------|---|
| Oral LD50 | Rat | 1530 mg/kg |
| Silica (CAS 7631-86-9) | | |
| Acute | | |
| Oral LD50 | Mouse | > 15000 mg/kg |
| | Rat | > 22500 mg/kg |
| Toluene (CAS 108-88-3) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | 12124 mg/kg 14.1 ml/kg |
| Inhalation | | |
| LC50 | Mouse | 5320 ppm, 8 Hours 400 ppm, 24 Hours |
| | Rat | 26700 ppm, 1 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours |
| Oral LD50 | Rat | 2.6 g/kg |
| Xylene (CAS 1330-20-7) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 43 g/kg |
| Inhalation | | |
| LC50 | Mouse | 3907 mg/l, 6 Hours |
| | Rat | 6350 mg/l, 4 Hours |
| Oral LD50 | Mouse | 1590 mg/kg |
| | Rat | 3523 - 8600 mg/kg |

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

| | |
|--|---|
| Crystalline Quartz Regulatory (CAS 14808-60-7) | 1 Carcinogenic to humans. |
| Ethylbenzene (CAS 100-41-4) | 2B Possibly carcinogenic to humans. |
| Silica (CAS 7631-86-9) | 3 Not classifiable as to carcinogenicity to humans. |
| Titanium Dioxide (CAS 13463-67-7) | 2B Possibly carcinogenic to humans. |
| Toluene (CAS 108-88-3) | 3 Not classifiable as to carcinogenicity to humans. |
| Tremolite (Non-asbestiform) (CAS 14567-73-8) | 1 Carcinogenic to humans. |
| Xylene (CAS 1330-20-7) | 3 Not classifiable as to carcinogenicity to humans. |

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Tremolite (Non-asbestiform) (CAS 14567-73-8) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline Quartz Regulatory (CAS 14808-60-7) Known To Be Human Carcinogen.

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Known To Be Human Carcinogen.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

| Components | | Species | Test Results |
|---|------|---|------------------------------|
| Acetone (CAS 67-64-1) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 10294 - 17704 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 4740 - 6330 mg/l, 96 hours |
| Ethylbenzene (CAS 100-41-4) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 1.37 - 4.4 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) | 7.5 - 11 mg/l, 96 hours |
| Naphtha, Petroleum, Heavy Alkylate (CAS 64741-65-7) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia pulex) | 2.7 - 5.1 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 8.8 mg/l, 96 hours |
| | | | 8.8 mg/l, 96 hours |
| Titanium Dioxide (CAS 13463-67-7) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | > 1000 mg/l, 48 hours |
| Fish | LC50 | Mummichog (Fundulus heteroclitus) | > 1000 mg/l, 96 hours |
| Toluene (CAS 108-88-3) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 5.46 - 9.83 mg/l, 48 hours |
| Fish | LC50 | Coho salmon,silver salmon (Oncorhynchus kisutch) | 8.11 mg/l, 96 hours |
| Xylene (CAS 1330-20-7) | | | |
| Aquatic | | | |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | 7.711 - 9.591 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

| | |
|----------------------|------------|
| Acetone | -0.24 |
| Dibutyltin Dilaurate | 3.12 |
| Ethylbenzene | 3.15 |
| Toluene | 2.73 |
| Xylene | 3.12 - 3.2 |

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

| | |
|--|--|
| Disposal instructions | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Local disposal regulations | Dispose in accordance with all applicable regulations. |
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. |

14. Transport information

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

| | |
|---|--|
| DOT | |
| UN number | UN1263 |
| UN proper shipping name | Paint related material including paint thinning, drying, removing, or reducing compound |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Label(s) | 3 |
| Packing group | II |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Special provisions | 149, B52, IB2, T4, TP1, TP8, TP28 |
| Packaging exceptions | 150 |
| Packaging non bulk | 173 |
| Packaging bulk | 242 |
| IATA | |
| UN number | UN1263 |
| UN proper shipping name | Paint related material (including paint thinning or reducing compounds) |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Packing group | II |
| Environmental hazards | No. |
| ERG Code | 3L |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Other information | |
| Passenger and cargo aircraft | Allowed. |
| Cargo aircraft only | Allowed. |
| IMDG | |
| UN number | UN1263 |
| UN proper shipping name | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Packing group | II |
| Environmental hazards | |
| Marine pollutant | No. |
| EmS | F-E, S-E |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not established. |

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Tremolite (Non-asbestiform) (CAS 14567-73-8) 0.1 % Annual Export Notification required.

CERCLA Hazardous Substance List (40 CFR 302.4)

| | |
|--|---------|
| Acetone (CAS 67-64-1) | Listed. |
| Ethylbenzene (CAS 100-41-4) | Listed. |
| Phosphoric Acid Regulatory (CAS 7664-38-2) | Listed. |
| Toluene (CAS 108-88-3) | Listed. |
| Tremolite (Non-asbestiform) (CAS 14567-73-8) | Listed. |
| Xylene (CAS 1330-20-7) | Listed. |

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

| | |
|--|----------------|
| Tremolite (Non-asbestiform) (CAS 14567-73-8) | Cancer Lung |
|--|----------------|

Superfund Amendments and Reauthorization Act of 1986 (SARA)

| | |
|--------------------------|------------------------|
| Hazard categories | Immediate Hazard - Yes |
| | Delayed Hazard - Yes |
| | Fire Hazard - Yes |
| | Pressure Hazard - No |
| | Reactivity Hazard - No |

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. |
|-----------------------------|------------|----------|
| Toluene | 108-88-3 | 5 - < 10 |
| Ethylbenzene | 100-41-4 | 0 < 5 |
| Tremolite (Non-asbestiform) | 14567-73-8 | 0 - < 5 |
| Xylene | 1330-20-7 | 0 - < 5 |

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylbenzene (CAS 100-41-4)
Toluene (CAS 108-88-3)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

Toluene (CAS 108-88-3) 594

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)

Crystalline Quartz Regulatory (CAS 14808-60-7)

Ethylbenzene (CAS 100-41-4)

Naphtha, Petroleum, Heavy Alkylate (CAS 64741-65-7)

Phosphoric Acid Regulatory (CAS 7664-38-2)

Solvent Naphtha, petroleum, light aromatic (CAS 64742-95-6)

Talc (CAS 14807-96-6)

Titanium Dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Xylene (CAS 1330-20-7)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Crystalline Quartz Regulatory (CAS 14808-60-7)

Ethylbenzene (CAS 100-41-4)

Naphtha, Petroleum, Heavy Alkylate (CAS 64741-65-7)

Phosphoric Acid Regulatory (CAS 7664-38-2)

Silica (CAS 7631-86-9)

Talc (CAS 14807-96-6)

Titanium Dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Crystalline Quartz Regulatory (CAS 14808-60-7)

Ethylbenzene (CAS 100-41-4)

Naphtha, Petroleum, Heavy Alkylate (CAS 64741-65-7)

Phosphoric Acid Regulatory (CAS 7664-38-2)

Silica (CAS 7631-86-9)

Talc (CAS 14807-96-6)

Titanium Dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Crystalline Quartz Regulatory (CAS 14808-60-7)

Ethylbenzene (CAS 100-41-4)

Naphtha, Petroleum, Heavy Alkylate (CAS 64741-65-7)

Phosphoric Acid Regulatory (CAS 7664-38-2)

Silica (CAS 7631-86-9)
 Talc (CAS 14807-96-6)
 Titanium Dioxide (CAS 13463-67-7)
 Toluene (CAS 108-88-3)
 Tremolite (Non-asbestiform) (CAS 14567-73-8)
 Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Acetone (CAS 67-64-1)
 Ethylbenzene (CAS 100-41-4)
 Phosphoric Acid Regulatory (CAS 7664-38-2)
 Toluene (CAS 108-88-3)
 Tremolite (Non-asbestiform) (CAS 14567-73-8)
 Xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

| | |
|--|---------------------------|
| Crystalline Quartz Regulatory (CAS 14808-60-7) | Listed: October 1, 1988 |
| Ethylbenzene (CAS 100-41-4) | Listed: June 11, 2004 |
| Titanium Dioxide (CAS 13463-67-7) | Listed: September 2, 2011 |
| Tremolite (Non-asbestiform) (CAS 14567-73-8) | Listed: February 27, 1987 |

US - California Proposition 65 - CRT: Listed date/Developmental toxin

| | |
|------------------------|-------------------------|
| Toluene (CAS 108-88-3) | Listed: January 1, 1991 |
|------------------------|-------------------------|

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

| | |
|------------------------|------------------------|
| Toluene (CAS 108-88-3) | Listed: August 7, 2009 |
|------------------------|------------------------|

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|-------------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | No |
| Canada | Domestic Substances List (DSL) | No |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | No |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | No |
| New Zealand | New Zealand Inventory | No |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | No |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
 A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Version 2.0
Revision Date 11/08/2020

Disclaimer

Our company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.